

PAVEMENT MARKERS, MARKINGS AND STRIPING

Markings – Left or Right Arrow Shared Left Through or Through Right Arrow Shared Left Right Arrow Shared Left Through Right Arrow Bike Lane Arrow (white) [skid resistant] [△] Bike Lane Symbol (white) [skid resistant] Railroad Crossing Symbol Pavement Words (Various) 24" Bar/Ladder Crosswalk [skid resistant]	Type III (L) or (R) Type II (L) or (R) Type III (B) Type II (B)	A24B A24B A24B A24B A24A A24C A24C A24D, A24E A24C
-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------	----------------------------------------------------------------------------

**CA MUTCD
Std. Plan**

Special Signs – Fluorescent Yellow, Green Sign Faces should be used for pedestrian warning, bicycle warning, playground warning, school bus and school warning. Markings – Shared Lane Marking [skid resistant]	W11A-2, W16-7P, W16-9P, W54A, W64, W65, W65-1, W66, W66A, W80, SI-1, S2-1, S2-1B, S4-3 Fig. 9C-9
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------

NOTES:

1. All traffic striping and pavement markings shall be thermoplastic unless otherwise noted.
2. Markings noted as [skid resistant] shall be Skid Resistant Thermoplastic or Flint Trading, Inc. "PreMark" ViziGrip. 336-475-6600 www.flintrtrading.com
3. Yellow paint for [△]median islands – two (2) coats per State of California Department of Transportation Standard Specifications Section 84-3
- [△]4. The following striping details to be used as alternates at problem locations where it is difficult to place and maintain striping due to moisture, sand, etc.:
 Detail 4 alternate to Detail 2
 Detail 23 alternate to Detail 22,
 Detail 30 alternate to Detail 29

ACAD FILE NO.C3101D616B Rev2.DWG

CITY OF SAN LEANDRO * STANDARD PLANS

NO.	REVISIONS	DATE	BY	STANDARD PAVEMENT DELINEATIONS	APPROVED
[△]	Revised note 4 deleted "Detail 1 alternate to Detail 2", & "Detail 21 alternate to Detail 22"	4/25/14	RLC		 Kenneth Joseph City Engineer R.C.E. No.34870 Expires 9/30/15
DRAWN	CHECKED	DATE	SCALE	SHEET	DWG. NO.
AMS	KJ/KRC	November 2013	NONE	2 OF 2	616B CASE. 3101