


**NOTES:**

1. All work shall be done in accordance with the Standard Specifications for Public Works Construction, the "GREENBOOK", the most current edition and all supplements thereto, adopted by the Southern California Chapter of the American Public Works Association and the Special Provisions (Technical Specifications) thereto adopted by the City.
2. Install Pepco Octa-Bubbler #2135 plug on unused outlets.
3. All threaded pipe and fittings shall be Schedule 80 PVC. Solvent welded pipe and fittings shall be Schedule 40 PVC. Approved teflon based pipe compound shall be used on all threaded connections.
4. Bury Quadra-Bubbler tubing 100mm (4") below grade.
5. Refer to Dwg. 428 Case 3101 for Drip Emitter Layout.

ACAD FILE NO. C3101D426 Rev1.dwg

**CITY OF SAN LEANDRO \* STANDARD PLANS**

NO.	REVISIONS	DATE					APPROVED						
△	To Sch. 80 nipple To Sch. 40 TEE & ELL	10/31/06	<b>DRIP IRRIGATION EMITTER DETAIL</b>				 Kenneth Joseph, City Engineer R.C.E. No.34870 Expires 9/30/09						
DRAWN	GF/MLWH/VL	CHECKED	KJ/KRC	DATE	May 2002	SCALE	NONE	SHEET	1 OF 1	DWG. NO.	426	CASE.	3101