



Typical section where trees are located adjacent to curbing, sidewalk or other structures. Install where shown on plans

NOTES:

1. All work shall be done in accordance with the Standard Specifications for Public Works Construction, the "GREENBOOK", the most current edition and all supplements thereto, adopted by the Southern California Chapter of the American Public Works Association and the Special Provisions (Technical Specifications) thereto adopted by the City.
2. Root barrier shall be Deep Root Corp. UB 24-2 or approved equal. Use 4 panels min. or as required.
3. Top of root control barrier must be at T.C. or sidewalk grade (never below grade).
4. Position root control barrier against structure or as close to structure as possible.
5. During construction, the root control barrier can be placed against the inside of the forms.
6. The raised root deflectors must be facing inward (toward the tree).
7. Install per manufacturer's recommendations and specifications.

ACAD FILE: C31010442.DWG

CITY OF SAN LEANDRO * STANDARD PLANS

NO.	REVISIONS	DATE	LINEAR ROOT BARRIER			APPROVED
						<i>[Signature]</i> 6/24/02
						Kenneth Joseph, City Engineer R.C.E. No. 34870
						Expires 8/30/03
DRAWN	GF/MLWH/VL	CHECKED	KJ/KRC	DATE	May 2002	SCALE NONE
				SHEET	1 OF 1	DWG. NO. 442 CASE. 3101