

CITY OF SAN LEANDRO

NOTICE TO BIDDERS

SUBMIT BID TO: City of San Leandro Purchasing Department 835 East 14th Street San Leandro, CA 94577	FOR FURTHER INFORMATION CALL: Darryl Sweet, C.P.M. Purchasing Supervisor (510) 577-3377 fax (510) 577-3312 dsweet@ci.san-leandro.ca.us
--	---

BID NO: 05-06.009 through 05-06.018 AND 05-06.020	DATE MAILED: September 8, 2005	THIS QUOTATION MUST BE DELIVERED TO THE CITY BEFORE: 3:00 P.M. Thursday, October 6, 2005
--	--	--

QTY.	DESCRIPTION	UNIT PRICE	EXTENSION
Multiple	<p>VARIOUS CURRENT MODEL YEAR VEHICLES AND EQUIPMENT</p> <p>Notice to Bidders</p> <p>Provide new and unused vehicles and equipment in accordance with the attached vehicle specifications, and as listed on the itemized bid form. Each bid number will be awarded individually. If you do not wish to respond to a bid item, leave it blank or fill in "no bid" on the corresponding row.</p> <p>All bidders must submit with their proposal sufficient literature to show compliance with specifications. Any deviations from specifications must be clearly indicated in writing at the time the proposal is submitted. The City reserves the right to waive minor variations in specifications bid.</p> <p><u>Do not include sales tax in your bid.</u> 8.75% sales tax will be added to the purchase order and remitted with invoice payment.</p> <p>State your earliest delivery date as requested. (This date may be an important factor in award determination.)</p> <p>Each vehicle shall be completely serviced as recommended by the manufacturer prior to delivery to the City, and shall be delivered to the City with a <i>full tank of fuel</i>.</p> <p>Other agencies may piggyback on the prices, terms and conditions of this bid, if mutually agreed upon.</p> <p>The original report of sale shall accompany the vehicle upon delivery to the City. The name and address on the Dealer's report of sale shall read City of San Leandro, 835 E. 14th Street, San Leandro, California 94577.</p> <p>Sealed bids shall be received at the Purchasing Office, City Hall, 835 E. 14th Street, San Leandro, CA up to 3:00 p.m., on Thursday, October 6, 2005 at which time they will be publicly opened and read.</p>	SEE BID FORM	SEE BID FORM

Any bid may be withdrawn at any time prior to the time fixed for the opening of bids only by written request for the withdrawal of the bid filed with the City. The request shall be executed by the bidder or bidder's duly authorized representative. The withdrawal of a bid does not prejudice the right of the bidder to file a new bid. Whether or not bids are opened exactly at the time fixed in the public notice for opening bids, a bid will not be received after that time nor may any bid be withdrawn after the time fixed in the public notice for opening of bids.

As stated in Public Contract Code Section 5100 to 5108, inclusive (State Contract Act) concerning relief of bidders and in particular to the requirement therein, that if the bidder claims a mistake was made in his bid, the bidder shall give the City written notice within five (5) days after the opening of the bids of the alleged mistake, specifying in the notice, in detail how the mistake occurred.

All bidders shall verify if any addendum for this project has been issued by the City. It is the bidder's responsibility to ensure that all requirements of contract addendum are included in the bidder's submittal.

The award will be made to the lowest responsible bidder whose bid complies with the specifications in a manner satisfactory to the City's best interests as determined by the City. The right is reserved, as the interest of the City may require, to reject any or all bids, or to waive any informality or minor irregularity in the bids.

Payment shall be within 30 days following acceptance of bid items.

- Delivery shall be F.O.B. destination (the per vehicle price will be inclusive of delivery to the City)
- Complete delivery _____ days from order
- Cash Discount _____ in _____ days (may or may not be a factor in determining award)

To bid, complete and return a copy of the Request and the other required forms, sealed in the enclosed envelope. The envelope shall be marked with the project name and bid number. The bid must be received by the date and time shown in order to be considered. Please note that there is a one-day delay in mail delivery to City Hall by the U.S. Postal Service.

Delivery shall be to:
Public Works Service Center
14200 Chapman Road
San Leandro, CA 94577.

Firm _____
Address _____

By (Signature) _____

Date: _____
Phone: _____
FAX: _____
Print Name: _____

Title: _____



Darryl Sweet, C.P.M.
Purchasing Supervisor

ITEMIZED BID FORM

All units to be new, unused and current model year (2006).

Any row that is blank will be considered a “no bid” for that bid number.

No additional charges or fees will be paid above the amounts bid. Include any documentation fees, tire fees, delivery, etc. in the vehicle price.

City of San Leandro will correct any math errors made in “extended” prices. Price “each” will be the determining price if necessary.

Bid Number	Bid Title	Make/Model	Price EACH	Extended Price
05-06.009	One (1) Cab/Chassis w/ Chipper Body		\$	\$
05-06.010	One ¾-Ton 2WD Pickup Truck		\$	\$
05-06.011	One (1) 2WD, Cab/Chassis 1-Ton		\$	\$
05-06.012	One (1) Four-wheel Utility Truck		\$	\$
05-06.013	One (1) Four-Door Sedan		\$	\$
05-06.014	One (1) 2WD Cargo Van		\$	\$
05-06.015	One (1) Cab/Chassis w/ Aerial Lift		\$	\$
05-06.016	One (1) Single-Engine Broom-Type Sweeper		\$	\$
05-06.017	Six (6) 2WD Compact Pickup Trucks		\$	\$
05-06.018	Six (6) Police Package Patrol Sedans		\$	\$
05-06.020	One (1) 2WD Mini Van w/ windows all around		\$	\$

Bid 05-06.009
**ONE (1) CAB/CHASSIS, 2WD WITH CHIPPER BODY DUMP BED
MOUNTED**

The following specifications are minimum unless otherwise specified.

- Engine:** 6.0 liter gas with E.F.I.
- Transmission:** Electronically controlled four speed automatic with overdrive.
- Wheelbase:** 161 inches
- Cab to Axle:** 87 inches
- G.V.W.R.:** 10,000 lbs with dual rear wheels.
- Steering:** Factory installed, power assisted.
- Brakes:** Power assisted, front disc, rear drum with A.B.S.
- Electrical:**
- A. 12 volt system, with 100 amp alternator.
 - B. Maintenance free, heavy duty battery.
 - C. Standard AM/FM radio.
 - D. Factory installed heater and air conditioning.
- Cab:**
- A. Standard two-door cab.
 - B. Right and left side extendable rear view or West Coast style mirrors.
 - C. Exterior and interior to be factory painted manufacturer's standard white.
 - D. Seat to be bench type covered in vinyl, dark grey or tan.
 - E. Heavy duty, full width black vinyl floor mat.
 - F. Standard air bags.
 - G. Seat belts in all seating positions.

- Tires & Wheels:**
- A. Steel wheels with radial tires sized to accommodate GVW rating.
 - B. Full size spare to be provided with vehicle.

Chipper Dump Body

To be all steel construction with hydraulically operated hoist. Dump body control to be inside of cab and equipped with a “bed up” warning light.

- Dimensions:**
- A. Length to be 108 inches
 - B. Width to be 92 inches
 - C. Height to be 52 inches

- Dump body:**
- A. To be located 24 inches behind cab to allow for pass through tool box to be mounted between cab and dump body.
 - B. A Holland brand (or equivalent) pintle style, bolt on hitch, shall be mounted to reinforced rear frame, 18 inches above the ground at center of hitch, also provide two (2) ‘D’ rings for safety chains.
 - C. Equipped with all D.O.T. required lights including brake/tail/turn signal, marker, clearance and back-up.
 - D. Dump bed shall be equipped with an OSHA approved, 12 volt back-up alarm and seven (7) pin trailer plug with cover, wired to truck lights and located near pintle hitch.
 - E. Tailgate to be a “barn door” style with the ability to swing open a full 270 degrees and latch on the curbside of chipper body, tailgate height to be 20 inches.
 - F. To be painted white to match cab.

- Tool Box #1:**
- A. A pass through style tool box, to be constructed of steel with two (2) separate compartments inside and locking sealed doors on both sides.
 - B. Box to be mounted on top of frame rail directly behind truck cab and in front of dump body.

- C. Tool box to be painted white to match cab and dump body.
- D. Dimensions:
 - 1. Length to be 24 inches
 - 2. Height to be 52 inches
 - 3. Width to be 92 inches

Tool Box #2

- A. One (1) additional tool box to be mounted on the left side of truck under pass through tool box.
- B. 'T' handle locks and rubber door seals to be provided.
- C. Tool box to be painted white to match cab and dump body.
- D. Approximate Dimensions:
 - 1. Length to be 18 inches
 - 4. Height to be 18 inches
 - 5. Width to be 48 inches

Miscellaneous:

- A. One (1) maintenance manual for cab/chassis.
- B. One (1) maintenance manual for dump bed.
- C. Two (2) extra sets of keys for ignition/doors and tool boxes.
- D. Dump bed shall be equipped with mud flaps behind each set of rear wheels.
- E. Dump bed shall incorporate a single hanging step mounted on left side, below opening of tailgate to enable entry to inside of dump body.
- F. D.M.V. registration to be completed by successful bidder.

Warranty:

Standard manufacturer's warranty on chassis/cab.

Bid 05-06.010
ONE (1) ¾-TON 2WD PICK-UP TRUCK

The following specifications are minimum unless otherwise specified.

- Engine:**
- A. 5.3 liter V8 with E.F.I.
 - B. Heavy-duty cooling system
- Transmission:**
- A. Electronically controlled four speed automatic with overdrive
 - B. Auto trans. cooler
- Wheelbase:** 131 inches
- G.V.W.R.:** 8,600 pounds
- Steering:** Factory installed power assisted
- Brakes:** Factory installed power assisted with antilock
- Suspension:** Heavy-duty with trailering capability
- Electrical:**
- A. Standard AM/FM radio
 - B. Maintenance free heavy-duty battery
 - C. 100 amp alternator
 - D. Factory installed air conditioning
- Body:**
- A. 2 door regular cab with long box
 - B. Rear step bumper
 - C. Standard front bumper
 - D. Right and left outside rear view mirrors
 - E. 25 gallon single fuel tank
 - F. Trailer towing package
- Exterior:** To be factory painted manufacturer's standard white
- Interior:**
- A. Full bench type seat, in tan or grey vinyl

covering

- B. Floor covering, full black vinyl mat
- C. Seat belts at all seating positions
- D. Inside painted area to be color coordinated with exterior color and interior seat trim

Tires & Wheels:

- A. Blackwall radial tires sized to accommodate G.V.W.R.
- B. Full size spare mounted under vehicle
- C. Standard wheels and hub caps

Miscellaneous:

- A. One set maintenance manuals
- B. All equipment furnished as standard
- C. Two (2) extra sets of ignition/door keys
- D. DMV registration to be completed by successful bidder.

Warranty:

Specs: ABW_61305_2207_774

Standard manufacturer's warranty

Bid 05-06.011
ONE (1) CHASSIS/CAB 2WD, 1-TON

The following specifications are minimum unless otherwise specified.

- Engine:** A. Gas 6.0 liter W/EFI.
B. Heavy duty cooling system.
- Transmission:** A. Electronically-controlled 4-speed automatic with overdrive.
B. Cooler.
- Wheelbase:** 159 inches
- G.V.W.R.:** 10,000 pounds with dual rear wheels.
- Cab to Rear Axle:** 84 inches
- Steering:** Factory installed power assisted.
- Brakes:** A. Power assisted hydraulic.
B. Front disc, rear drum, with antilock.
C. Park brake.
- Battery:** Heavy duty maintenance free.
- Alternator:** Heavy duty 100 amp.
- Fuel Tank:** A. Dual tanks.
B. 35 gallon capacity.
- Electrical:** A. Gauges, speedometer, odometer, fuel, volt meter, temperature and oil.
B. Intermittent windshield wipers.
- Body/Cab:** A. Standard cab.
B. Exterior and interior areas to be factory painted standard white.
C. All interior trim to be grey or light brown.
- Body/Cab (cont'd):** D. Seat to be bench type covered in vinyl.

- E. Right and left outside rear view mirrors.
- F. Standard front bumper, no rear bumper.
- G. Standard heater/defroster.
- H. Inside hood release.
- I. Heavy duty, full width black vinyl floor mats.
- J. Standard AM/FM radio.
- K. Factory installed air conditioning.

Tires & Wheels:

- A. All season radials at all positions sized to match payload, G.V.W.R. of vehicle.
- B. Full-sized spare secured in frame mount under vehicle.
- C. Standard wheels and wheel covers.

Miscellaneous:

- A. D.M.V. registration to be completed by successful bidder.
- B. Two (2) extra sets of keys for door/ignition.
- C. One (1) each maintenance manual.

Warranty:

Standard manufacturer's warranty.

Specs: ABW_81205_2406_857

- Miscellaneous (cont'd):**
- D. Two extra sets of keys for ignition.
 - E. One set maintenance manuals.

Warranty: Standard manufacturer's warranty.
Specs: ABW_71205_2114_702

Bid 05-06.013
ONE (1) 2WD, 4-DOOR SEDAN

The following specifications are minimum unless other wise specified.

- Engine:** 3.0 litre V6 with E.F.I.
- Transmission:** 4 speed electronically controlled automatic with overdrive.
- Wheelbase:** 108 inches.
- Steering:** Factory installed power assisted.
- Brakes:**
- A. Factory installed power assisted; front disc, rear drum.
 - B. 4-wheel antilock brake system.
- Electrical:**
- A. Heavy-duty maintenance free battery.
 - B. 100 amp alternator.
- Body:** Standard manufacturer's four (4)-door.
- Tires & Wheels:**
- A. Black sidewall tires sized to match G.V.W.R.
 - B. Standard wheels and wheel covers.
- Exterior Finish:** Entire exterior to be factory painted in a color equal to **metallic dark green**.
- Interior Finish:** All trim to be color coordinated in a neutral color with exterior paint.
- Glass:**
- A. All glass to be factory tinted.
 - B. Factory provided power windows.

Seats & Interior:

- A. Standard seating with standard cloth trim.
- B. Front and rear carpeting to be coordinated with interior seat trim.
- C. Front and rear floor mats, color keyed with carpeting.
- D. Driver and passenger side air bags.

Miscellaneous:

- A. Factory installed air conditioning.
- B. Factory installed AM/FM/ radio.
- C. Right and left side outside rear view mirrors.
- D. Day and night inside rear view mirror.
- E. All safety equipment listed and advertised as standard.
- F. One (1) set maintenance manuals.
- G. Power door locks.
- H. Two (2) extra sets of keys for doors/ignition.

Warranty:

Specs: ABW_61705_1002_318

Standard manufacturer's warranty.

Bid 05-06.014
ONE (1) 2WD CARGO VAN

The following specifications are minimum unless other wise specified.

- Engine:**
- A. 5.3 liter V8
 - B. Heavy duty cooling system
 - C. Oil cooler
- Transmission:** Three-speed automatic with cooler.
- Wheelbase:** 138 inches
- G.V.W.R.:** 9,200 lbs
- Overall Length:** 231 inches
- Payload:** 3,475 lbs
- Steering:** Factory installed power assisted.
- Brakes:**
- A. Front wheel disc/rear drum.
 - B. Power assisted with A.B.S.
- Electrical:**
- A. Maintenance free 12 volt battery.
 - B. 95 amp alternator.
- Body:**
- A. Right and left outside rear view mirrors.
 - B. Standard front bumper, rear step bumper.
 - C. Rear right side door to be sliding type.
 - D. Dual rear doors with windows.
 - E. Windshield, front door windows, rear door windows, all to be tinted.
 - F. Heavy duty shock absorbers.
 - G. 35 gallon fuel tank.
- Exterior:** To be factory painted manufacturer's standard white.

Interior:

- A. Right and left front bucket seats only, in tan vinyl.
- B. Seat belts at front bucket seats only.
- C. Inside rear view mirror.
- D. Intermittent windshield wipers.
- E. Interior painted areas to be manufacturer's standard white.
- F. Rubber mats in front seating area only.
- G. Light in rear cargo area.
- H. Driver's side air bag.
- I. Standard AM/FM radio.
- J. Factory installed air conditioning and heating.

Tires & Wheels:

- A. Blackwall radial tires sized to accommodate G.V.W.R.
- B. Standard wheels and hub caps.
- C. Full size spare mounted under vehicle.

Miscellaneous:

- A. One set maintenance manuals.
- B. Two (2) extra sets of ignition/door keys.

Warranty:

Specs: ABW_61405_2214_856

Standard manufacturer's warranty.

Bid 05-06.015
ONE (1) CAB/CHASSIS WITH AERIAL LIFT

The following specifications are minimum unless otherwise specified.

- General:** Aerial lift to be mounted on a commercial current model year chassis/cab truck with fully finished rust protected service body. Aerial lift base to be mounted behind cab, forward of differential.
- Engine:**
- A. 6.0 liter diesel, 8 cylinders
 - B. 160 H.P.
 - C. Heavy duty cooling system
 - D. Dry type air cleaner with pre-cleaner
 - E. Full flow oil filter
 - F. Fuel filters, primary/secondary
- Transmission:**
- A. Electronic 4-speed automatic
 - B. Trans cooler
- Wheelbase:** 161 inches
- G.V.W.R.:** 12,000 lbs.
- Cab to Axle:** 84 inches
- Steering:** Power assisted
- Brakes:**
- A. Power assisted with A.B.S.
 - B. Hydraulic
 - C. Parking brake, separate or in combination with brake system
 - D. Disc brakes at front, drum at rear
- Electrical:**
- A. Dual batteries, 84 amp hour
 - B. 75 amp alternator
 - C. Back-up horn

- Electrical (cont'd):**
- D. All lighting to meet California and federal vehicle codes
 - E. Trailer towing wiring
 - F. Back-up lights
 - G. Factory installed AM/FM radio

- Body (Cab/Chassis):**
- A. Regular cab
 - B. West Coast type mirrors, left and right sides
 - C. Mud flaps behind rear wheels
 - D. Dual rear wheels
 - E. Exhaust system to exit behind rear wheels, preferably left side. Right side or vertical accepted.
 - F. 36 gallon capacity fuel tank

- Body (Utility):**
- A. Floor to be 12 gauge treadplate
 - B. Top of storage compartments to be treadplate
 - C. All handles to be flush mounted, with locks
 - D. Interior shelves to be adjustable, with adjustable dividers
 - E. Door to be sealed type, with drip rail at top
 - F. Storage compartment to have drains
 - G. Entire body to be undersealed
 - H. Door hinges to be length of door
 - I. All edges rolled or folded for safety
 - J. 20 inches from rear of chassis cab to front of utility body, this area will have steel diamond plate installed

- Hydraulic System:**
- A. Belt driven pump on prime mover engine
 - B. Hydraulic reservoir sized to support system demands. Constructed with internal baffles.
 - C. Return line filter
 - D. Holding valve on lift cylinder
 - E. Lower controls ability to override basket controls
 - F. Emergency boom lower capacity

- Aerial Lift:**
- A. Upper boom controls to be attached to basket
 - B. Working height, 30 ft.
 - C. Stowed height, 10 ft.
 - D. 300 lb. basket capacity
 - E. Upper boom, fiberglass, insulated
 - F. Torsion bar stabilizing
 - G. Basket entry step not to exceed 3 ft.
 - H. Square fiberglass bucket, insulated with liner
 - I. Hydraulic self-leveling bucket
 - J. Boom must meet ANSI standard for “Under 69KV” rating
 - K. Safety harness and lanyard in basket
 - L. Lower boom controls to be mounted on a stationary part of pedestal; these controls to have lights for night operation
 - M. Pedestal mounted work lights (4” diameter) right and left sides
- Exterior:**
- A. Exterior of prime mover and aerial device to be painted standard factory white
 - B. Aerial basket to be painted non-conducting orange
 - C. All under carriage components to be painted black
- Interior:**
- A. All painted area to match exterior color
 - B. All interior covered areas are to be tan
 - C. Vinyl-cover full width front seat
- Tires & Wheels:**
- A. Tire sized to match G.V.W.R. – blackwall, all season
 - B. Wheels, 8 hole disc, steel
 - C. One spare tire and wheel mounted on vehicle
 - D. One set (2) wheel chocks
- Miscellaneous:**
- A. 3,500 lb. 12 volt DC front mount electric winch, with remote control switches. Winch is to be attached to 2 inch steel box tubing, trailer receiver, that can be inserted into corresponding 2 inch inserts that are mounted on both the front and rear

of truck. Remote control power plugs are to be installed on both front and rear of truck to facilitate operating winch with the hand held remote. Winch should have free wheel capability with manual operation in the event of power loss. 50 ft. of cable on spool. Remote control is to be hand-held type that is removable for inside storage.

- B. One each service and parts manual for aerial device, and prime mover
- C. Trailer hitch, receiver insert type. 2 inch ball with bottom of ball 15 inches above ground
- D. Two (2) extra sets of keys for ignition/doors on cab chassis and tool boxes
- E. D.M.V. registration to be completed by successful bidder.

Warranty: Standard factory warranty on truck and aerial device

Specs: ABW_61305_2301_ADD

Bid 05-06.016
**ONE (1) SINGLE-ENGINE FOUR-WHEEL BROOM-TYPE STREET
SWEEPER**

The following specifications are minimum unless otherwise specified.

- Engine:**
- A. 6 cylinder diesel.
 - B. 190 horsepower @ 2500 RPM
 - C. All sweeper functions and drive systems powered by this engine.
- Transmission:**
- A. Allison automatic with manual range selection or auto four forward speeds, one reverse.
 - B. Auxiliary transmission with sweep and travel modes.
 - C. Vehicle governed speed to be 62 MPH.
- Wheelbase:** 132 inches
- G.V.W.R.:** 33,000 pounds
- Steering:**
- A. Factory installed power assisted, dual controls.
 - B. Manual steering capability.
- Brakes:**
- A. Power assisted four wheel disc.
 - B. Antilock.
- Electrical:**
- A. 12 volt system.
 - B. Dual heavy-duty maintenance free batteries, 1800 CCA total rating.
 - C. 160 amp alternator.
- Hopper:**
- A. Hopper capacity 4.25 cubic yards.
 - B. High lift dump type.
 - C. Lift mechanism, scissor type with hydraulic cylinders.
 - D. 9,000 pound lift capacity.

- Hopper (cont'd):**
- E. Maximum dump height – bottom of hopper 114 inches.
 - F. Dump controls operated from inside cab.

- Dirt Conveyor:**
- A. Squeegee type with replaceable rubber edging.
 - B. Elevator chain to be steel on rubber bushings.
 - C. Elevator jam warning device.
 - D. Elevator operated by a hydraulic motor, forward and reverse.
 - E. Elevator to be adjustable to compensate for chain wear.

- Water System:**
- A. 220 gallon water tank capacity.
 - B. Spray nozzles across front and over each gutter broom and pick-up broom.
 - C. Independent control valves.
 - D. Water fill equipped with 2.5 inch NST hydrant coupling.

- Cab:**
- A. Shall be fully enclosed and of all steel construction.
 - B. Left and right side seats to be covered in black vinyl, equipped with seat belts and arm rests.
 - C. Rear view mirrors mounted on the left and right side of hood, with additional convex style mirrors mounted on both sides on the front of hood.
 - D. Cab to be insulated to minimize noise level.
 - E. Floor covering, full black vinyl mat.
 - F. Inside painted area to be color coordinated with exterior color.

- Gutter Brooms:**
- A. Mounted right and left side.
 - B. 44 inch diameter.
 - C. Hydraulically driven with adjustment for tilt, pressure and wear.
 - D. Hydraulic lift control from inside cab.
 - E. Four segment plastic disposable type.
 - F. Air broom pressure controls inside cab.

- Pick-up Brooms:**
- A. 32 inch diameter, 58 inches in length.
 - B. Broom drive hydraulically driven with relief valve protection.
 - C. Broom to be hydraulically lowered and raised by in-cab controls.
 - D. Air broom pressure controls inside cab.

Exterior: To be factory painted manufacturer's standard white.

Fuel Tank: 50 gallon capacity.

- Miscellaneous:**
- A. Factory installed air conditioning.
 - B. Factory installed AM/FM radio.
 - C. One each spare tire and wheel to fit both axles.
 - D. One each operator parts and maintenance manuals.
 - E. Successful vendor to provide technical and operator training within 10 days of delivery.
 - F. Two extra sets of keys for ignition/doors.
 - G. D.M.V. registration to be completed by successful bidder.

Warranty: Standard manufacturer's warranty.

Specs: ABW_7505_2503_851

Bid 05-06.017
SIX (6) 2WD COMPACT PICK-UP TRUCKS

The following specifications are minimum unless other wise specified.

- Engine:**
- A. 3.0 litre V6 with E.F.I.
 - B. Heavy-duty cooling system.
- Transmission:**
- A. Electronically controlled four-speed automatic with overdrive.
 - B. Auto trans. cooler.
- Wheelbase:** 116 inches.
- G.V.W.R.:** 4,900 pounds.
- Steering:** Factory installed power assisted.
- Brakes:**
- A. Power assisted front disc, rear drum.
 - B. Antilock.
- Electrical:**
- A. Standard AM/FM radio.
 - B. Maintenance free heavy-duty battery.
 - C. 100-amp alternator.
 - D. Factory installed air conditioning.
- Body:**
- A. 2-door regular cab.
 - B. Rear step bumper.
 - C. Standard front bumper
 - D. Right and left outside rear view mirrors.
 - E. 20-gallon single fuel tank.
- Exterior:** To be factory painted manufacturers standard white.
- Interior:**
- A. Full width bench type seat, in tan or grey vinyl covering.
 - B. Floor covering, full black vinyl mat.
 - C. Seat belts at all seating positions.

Interior (cont'd)

- D. Standard air bags.
- E. Inside painted area to be color coordinated with exterior color and interior seat trim.

Tires & Wheels:

- A. Blackwall radial tires sized to accommodate G.V.W.R.
- B. Full size spare mounted under vehicle.
- C. Standard steel wheels and hub caps.

Miscellaneous:

- A. One set maintenance manuals.
- B. All equipment furnished as standard.
- C. Two (2) extra sets of keys for door/ignition.
- D. D.M.V. registration to be completed by successful bidder.

Warranty:

Standard manufacturer's warranty.

Specs: ABW_61405_2103_753,785,667,664,662,665

Bid 05-06.018
SIX (6) POLICE PATROL PACKAGE SEDANS

The following specifications are minimum unless other wise specified.

- Engine:**
- A. 4.6L fuel injected (police package).
 - B. Heavy duty cooling system w/ reservoir.
 - C. Silicone hoses w/ screw type hose clamps.
 - D. Alternator 130 amp output, heavy duty (police package).
 - E. Engine oil cooler.
 - F. High performance drive belts.
 - G. Exhaust system stainless steel, dual.
- Transmission:**
- A. 4 forward, 1 reverse automatic with over drive.
 - B. Oil cooler.
- Differential:**
- The differential shall be a conventional type ring and pinion gears, with limited slip capacity. A ratio designed to give best overall performance for transmission and tire size installed on vehicle. The gear ratio shall be the same on all vehicles delivered on this bid.
- Steering:**
- A. Power assisted.
 - B. Tilt steering wheel color coordinated with interior, to include air bag.
 - C. Power steering fluid external cooler.
- Brakes:**
- A. Power assisted.
 - B. Disc brakes at all four wheels, anti-locking.
 - C. Heavy duty police package pads.
 - D. Manual release park brake, rear wheel actuated.
- Suspension:**
- The front and rear suspension, including shock absorbers, shall be heavy duty, and designed for police patrol vehicle. Also included must be heavy duty front and rear stabilizer bars.
- Wheelbase:** 114 inches.

Body:

- A. Four door sedan with center post.
- B. No exterior molding on front doors, and no molding holes.
- C. Exterior color to be black, with exception of roof and front doors which are to be white. Paint must be factory applied.
- D. Interior painted areas must be color coordinated with tan cloth and vinyl seats, or grey as an alternate.
- E. Heavy duty rubber floor mats, front and rear (black).
- F. Inside hood release.
- G. Inside rear deck release with switch located on right side of steering column, lower portion of dashboard.
- H. Right & left electrically controlled outside rear view mirrors.
- I. Inside rear view mirror to be “day/night” type view mirrors.
- J. Fuel tank to be minimum 19 gallons.
- K. Arm rests on all four doors.
- L. Tinted glass on windows.
- M. Driver and passenger side air bags.
- N. Roof enforcement for roof mounted equipment.

Electrical:

- A. Spot lights, right & left side, pillar mounted.
- B. Gauges, volt meter, oil pressure, water temperature, fuel level.
- C. All electrical equipment shall be shielded to minimize radio interference.
- D. Ground straps are required on the following:
 - Rear bumper to frame
 - Hood to body
 - Trunk lid to body
 - Frame to body if separate
 - Exhaust pipe to body
 - Engine to frame
- E. Alternator 130 amp, with 65 amp at idle in park.

- Electrical (cont'd):**
- F. Battery to be heaviest duty type compatible with charging system.
 - G. Door locks, controlled from drivers & front passenger positions.
 - H. Cigarette lighter in front compartment only.
 - I. Halogen head lamps, both high and low beams.
 - J. Rear window defogger/defroster.
 - K. Power windows lockout switch at driver's position; rear window switches inoperable.
 - L. Rear deck lid release.

- Seating:**
- A. Power driver's seat; passenger seat manually adjustable.
 - B. Front seats shall be heavy duty bucket seats.
 - C. Trim to be cloth with vinyl. Tan light brown or grey as alternate.
 - D. Rear seat heavy duty vinyl.

- Tires & Wheels:**
- A. All five tires must be high speed rated (130 mph).
 - B. Tires and wheels must be sized to police vehicle requirement; wheels must not be less than 15 inch x 6.5 inch.
 - C. Wheels to be factory painted black, fitted with hub caps, **not wheel covers**.
 - D. Full size spare tire and wheel.

- Miscellaneous:**
- A. Factory installed air conditioning.
 - B. Air conditioning high speed pressure cut out.
 - C. Fresh air type heater/defroster.
 - D. Glove box with lock.
 - E. Single key operations for vehicles locks/ignition; all vehicles keyed alike.
 - F. Front license plate bracket.
 - G. Speedometer certified calibration, 2 mph increments; 140 indication.
 - H. Intermittent windshield wiper system.
 - I. Passive restraint front seat belts.
 - J. Factory installed AM/FM radio.

- Miscellaneous :**
- K. One set each parts and maintenance manuals, in book form or CD-Rom format, which ever is available.
 - L. Trunk pack option, Code #14T.
 - M. D.M.V. registration to be completed by successful bidder.

Warranty: Standard manufacturer's warranty.

Vehicles not placed in service immediately upon receipt shall be warranted from the date the unit is placed into service.

Specs: ABW_61305_1104

Bid 05-06.020

ONE (1) 2WD MINI VAN WITH WINDOWS ALL AROUND

The following specifications are minimum unless otherwise specified.

- Engine:** 3.4L V6 with EFI.
- Transmission:** Four speed automatic with overdrive.
- Wheelbase:** 120 inches.
- Cargo Space:** 130 cubic feet.
- Payload:** 1,600 pounds.
- Steering:** Factory installed power assisted.
- Brakes:**
- A. Factory installed power assisted. Disc front, drum rear.
 - B. Anti-lock braking system.
- Electrical:**
- A. Standard AM/FM radio.
 - B. Maintenance free battery.
 - C. Factory installed heating and air conditioning.
- Body:**
- A. Right and left low mount outside rear view mirrors.
 - B. Tinted glass at all locations.
 - 1. ¼ panels right and left with glass.
 - 2. Rear door/doors with glass.
 - 3. Right side sliding door with glass.
 - 4. 25 gallon, single fuel tank.
- Exterior Finish:** Factory painted standard white.

- Interior:**
- A. Driver's side air bag.
 - B. Two front seats, one single, second row bench seat, cloth covered in tan or grey. Total seating for five (5).
 - C. Full length head liner.
 - D. Color keyed full length carpet.
 - E. Inside painted area to be color coordinated with exterior color and interior seat trim.

- Tires & Wheels:**
- A. Blackwall tires compatible with G.V.W.R.
 - B. Spare mounted under vehicle.
 - C. Standard wheels and hub caps.

- Miscellaneous:**
- A. One set maintenance manuals.
 - B. Two extra sets of keys for doors/ignition.
 - C. D.M.V. registration to be completed by successful bidder.

Warranty: Standard manufacturer's warranty.